



KPC136DT 21 LEDs IR Camera



FEATURES

- (1) Cable management to hide the cable in the bracket for cable damage prevention
- (2) High sensitivity in the dark environment, 0.05Lux / F2.0, 0Lux (IR ON)
- (3) Day and night features for 24-hour surveillance
- (4) Excellent image quality
- (5) IR LED effective range reaches up to 15 meters
- (6) IP66 standard approved outdoor housing

SPECIFICATIONS*

MODEL	KPC136DT
Pick up Element	1/3" color CCD image sensor
Number of Pixel	512(H) x 492(V) <ntsc> / 512(H) x 582(V) <pal></pal></ntsc>
Resolution	400 TVL
Min. Illumination	0.05Lux / F2.0, 0Lux (IR ON)
IR LED	21 units
Effective Range	Up to 15 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6 °
IRIS Mode	AES
White Balance	ATW
IP Rating	IP66
Video Output	1.0 ∨p-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption (±10%)	90mA (IR OFF), 280mA (IR ON)
Dimensions (mm)**	116.13(L) x 60(W) x 79.58(H)

^{*} The specifications are subject to change without notice.

^{**} Dimensional Tolerance: ± 5mm