The first Embedded facial recognition system in the world





- > Accurate
- > Standalone
- > User Friendly
- > Reliable performance
- > Multi-factor Authentication





> Trackable

> Contactless








CM i F21

The first Embedded facial recognition system in the world

System Configuration:







Processor	TI DM CPU 600MHz
User Capacity	500 Users
Record Capacity	150,000 Records
Recognition Algorithm	Dual Sensor TM V2.0
Sensor	Specialized double sensor
Verification Method	Face,Pin+Face,Card,Card+Face,Card+Photo
Verification Speed	Less than 1 Second (500 Users)
Keyboard	4*4 Touch Keypad
	3.5 inch TFT Color Screen
LCD	65,000 Bright Color
	320*240 Resolution
Communication	Standard TCP/IP
Method	USB Host
Power	12V DC, Working Current 500 mA
Environment Light	0-5000Lux
Working Distance	30-80cm
Working Temperature	0℃-40℃
Working Humidity	20% - 80%
Size	200* 95* 115 mm
Weight	505g
Installation Method	Wall Mounting
Security Image Capacity	4GB SD Card, 70,000 images
Card Recognition	Standard EM, Optional Mifare
Security Alarm	Tamper Alarm
Output for Access	Standard Wiegand 26/34 output、Built-in relay
Control System	
Certification	CE FCC Class A ROHS









