# The first Embedded facial recognition system in the world







- > Accurate
- > Trackable
- > Standalone
- > Contactless
- > User Friendly
- > Reliable performance
- > Multi-factor Authentication











## The first Embedded facial recognition system in the world

#### Features:



#### Embedded facial recognition system

- Adopt US advanced DSP technology keeps processing and matching right on
- Standalone application as Time attendance, Access control, User identification



#### User friendly design

- 3.5 inch color screen for face positioning
- · Contactless authentication for the

**High Usability and Security** • Failure to enroll and acquire rate is less

• Incident trackable for security with photo

Voice prompt



# Accurate and Fast Identifica-

- Industrial Leading "Dual Sensor" Facial Recognition Algorithm, FAR<0.0001%</li>



99.999%

# Reliable performance under different environments

- Different source-light Technology
- The system can work in different light condition even in the dark
- Over 20 months market testing



#### Large user and log capacity

- 500 user for 1:N
- Over 150,000 logs



#### Flexible I/O interfaces

- Internet Protocol based enables LAN or
- USB Host for User data upload or download via USB flash driver




#### **Multi Authentication**

System can work with Face, Pin+Face



# CM i F20

### **System Configuration:**



## Standalone or LAN System T&A software Access control software Flash Driver Admin Admin Ethernet (TCP/IP) Flash Driver Flash Driver Staff Time attendance and access Time attendance terminal control terminal

#### **Technical Specification**

	CMF 605
Processor	TI DM CPU 600MHz
User Capacity	500 Users
Record Capacity	150,000 Records
Recognition Algorithm	Dual Sensor TM V2.0
Sensor	Specialized double sensor
Verification Method	Face,Pin+Face
Verification Speed	Less than 1 Second (500 Users)
Keyboard	4*4 Touch Keypad
	3.5 inch TFT Color Screen
LCD	65,000 Bright Color
	320*240 Resolution
Communication	Standard TCP/IP
Method	USB Host
Power	12V DC, Working Current 500 mA
Environment Light	0-5000Lux
Working Distance	30-80cm
Working Temperature	0°C−40°C
Working Humidity	20% - 80%
Size	200* 95* 115 mm
Weight	505g
Installation Method	Wall Mounting
Security Image Capacity	
Card Recognition	
Security Alarm	
Output for Access	
Control System	
Certification	CE FCC Class A ROHS











